

# Submittal Data: System 12RLS ASU12RLS & AOU12RLS



Job Name: \_\_\_\_\_ Location: \_\_\_\_\_  
 Purchaser: \_\_\_\_\_  
 Engineer: \_\_\_\_\_  
 Submitted To: \_\_\_\_\_ For:  Reference  Approval  Construction  
 Submitted By: \_\_\_\_\_  
 Unit Designation: \_\_\_\_\_ Schedule No. \_\_\_\_\_ Model No.: \_\_\_\_\_

### Capacities:

Cooling	12,000 BTU/h
Outdoor Design Temp. <i>F° DB/WB</i>	95/75
Heating	16,000 BTU/h
Outdoor Design Temperature <i>F° DB/WB</i>	47/43
HSPF	12
SEER	25.0
EER <i>Cooling/Heating</i>	14.46/13.33
Voltage/Frequency/Phase	208-230/60/1

### Indoor Unit:

Noise Level Cooling <i>db (A) - H/ M/ L/ Q</i>	46/ 41/ 33/ 24
Noise Level Heating <i>db (A) - H/ M/ L/ Q</i>	46/ 41/ 33 /24
Weight	24 lbs.

### Outdoor Unit:

Noise Level <i>Cooling/Heating</i>	49/50
Recommended Fuse Size	15A
Min. Ampacity	10A
Running Current <i>Cooling</i>	3.9A
Running Current <i>Heating</i>	5.5A
Weight	88 lbs.

### Refrigerant Piping:

Max Ht. Difference	49 ft.
Max Total or Combined Length	66 ft.
Discharge Vapor Line (O.D.)	1/4 in.
Suction (O.D.)	3/8 in.

- ◆ Six year compressor warranty
- ◆ Two year parts warranty
- ◆ Digital wireless remote control
- ◆ 4-way automatic louvers
- ◆ Min Heat (50F heating set point)
- ◆ Built in Low Ambient
- ◆ Auto Restart/ Reset
- ◆ 24 hour timer
- ◆ Optional Wired Remote Control
- ◆ Dry mode
- ◆ Refrigerant R410A
- ◆ Quiet Mode

### Notes:

---



---



---

### OUTLINE AND DIMENSIONS

