A Carbon Filter That Removes Objectionable Tastes & Odors

- Available with molded 1/4" FPT openings (4617-24), including a special tapered "starter" thread that allows for easier threading of fittings.
- Ultrasonic spin welding process provides for a uniformly, hermetically sealed filter.
- Rated Service Life: 750 gallons; replace every 5-6 months.
- Pressure; 20 psi minimum and 125 psi maximum.
- Maximum temperature; 100°F.
- Flow Rate: 1.0 gpm.

Ice Machine Flltration

Micro-Carbon 4



Description

The Micro-Carbon 4 utilizes a standard 12" x 40" mesh washed carbon, which is rated at a nominal 20 micron filter capability. It is designed to remove objectionable tastes and odors, such as those caused by chlorine, hydrogen sulfide ("rotten egg"), iron, etc. One unit will typically last for 5-6 months.

Applications

- Ice Makers
- Water Fountains
- · Coffee Urns and Brewers
- Beverage Makers
- Other equipment where taste and odor is a concern

Tested and listed to ANSI/NSF Standard 42 for taste, odor and chlorine reduction, CLASS I.

DO NOT USE WHERE THE WATER IS MICROBIOLOGICALLY UNSAFE OR WITH WATER OF UNKNOWN QUALITY WITHOUT ADEQUATE DISINFECTION BEFORE OR AFTER THE UNIT

Read and understand the product's label and Material Safety Data Sheet ("MSDS") for precautionary and first aid information.

The MSDS is available on the Nu-Calgon website at www.nucalgon.com or is returnable by U.S. Mail upon request.

