

Boiler Relay, On-Off

Submittal Information

Revision A: July 15, 2008

Project Information

Job Name:

Location:

Part No. Ordered:

Engineer:

Date Submitted:

Contractor:

Submitted By:

Manufacturer's Representative:

Approved By:

Technical Data

Power:	10VDC at 10mA
Control:	Boiler Relay (two-stage)
Enclosure:	Mounts on a standard ¾" electrical knockout
Contact Rating:	120VAC, 2 Amp
Ambient Conditions:	32°F to 105°F (0°C to 41°C) 10% to 90% humidity no condensing
Connections:	RJ45 connectors
LED TT-A:	Illuminates when the first stage is commanded On.
LED TT-B:	Illuminates when the second stage is commanded On.
LED Power:	Illuminates when the Network System commands TT-A or TT-B On.



Product Information and Application Use

The Climate Cöntrol™ Multifunction or Climate Cöntrol Network system controls and stages up to two boilers per relay.

✓	Description	Part Number	Height	Width	Depth	Weight
☐	Boiler Relay, On-Off	A9012010	1.50"	3.00"	2.50"	0.25 lbs.

Installation

Mount on or near the boiler. Connect using a standard Cat5 cable with RJ45 ends. Refer to the Uponor Climate Cöntrol Network System Boiler Relay Instruction Sheet for additional information.

Standards

Class II wiring

Codes

N/A

Listings

N/A

Related Applications

Radiant Heating and Cooling System
Snow and Ice Melting System
Permafrost Protection System
Turf Conditioning System

Contact Information

Uponor, Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
Phone: (800) 321-4739
Fax: (952) 891-2008
www.uponor-usa.com

Uponor Ltd.
655 Park Street
Regina, SK S4N 5N1 CANADA
Phone: (888) 994-7726
Fax: (800) 638-9517
www.uponor.ca