

Model P3000BR

Pressure Safety Relief Valves

SPECIFICATION SUBMITTAL SHEET



FEATURES

Sizes: □ 3/4" □1" □ 1 1/4" □ 1 1/2" □ 2"

Connections: Female NPT inlet and outlet


Pressure Setting Range 30-150 PSI Temperature Rating 212° F

ACCESSORIES

- Expansion tank (Model WXTP)
- ☐ Water pressure reducing valve (Model 80CI)
- ☐ Backflow Preventer (Model 760)

DIMENSIONS & WEIGHTS (do not include pkg.)

	DIMENSIONS (approximate)							SHIPPING	
SIZE	Α		В		C		WEIGHT		
	in.	mm	in.	mm	in.	mm	lbs.	kg	
3/4" X 3/4"	1 1/2	38	3 1/4	83	1 3/4	45	1 1/3	0.6	
1" X 1"	1 5/8	41	4 7/16	113	1 1/8	29	2 1/3	1.0	
1 1/4" X 1 1/4"	2 1/16	52	5 7/8	149	1 1/2	38	3 1/3	1.5	
1 1/2" X 1 1/2"	2 15/32	63	5 7/8	149	1 5/8	41	4 1/3	2.0	
2" X 2"	3	76	7	178	2 7/8	73	4 1/3	2.0	



APPLICATION

Designed for use on hot water space heating boilers, water supply heaters and storage tanks. These valves are designed for use on hot or cold water service only and are not to be used for steam.

STANDARDS COMPLIANCE

■ ASME listed and rated






MATERIALS

Main valve body
Seat disc
Diaphragm
Cast Bronze
Silicone
EPDM

Springs Stainless Steel, 300 Series

TYPICAL INSTALLATION

Local codes shall govern installation requirements. Unless otherwise specified, the relief valve shall be installed in accordance with manufacturers' instructions and the latest edition of the Uniform Plumbing Code ®. <u>CAUTION</u>: Relief valves are designed to discharge water, should the proper conditions arise. In order to prevent water damage, relief valves must be plumbed outside the building or to an approved, safe drain as described by the Uniform Plumbing Code.



A.S.M.E. RELIEF CAPACITIES AT STANDARD SETTINGS BTU/HR STEAM RELIEF										
Relief Settings	3/4" x 3/4"	1" x 1"	1 1/4" x 1 1/4"	1 1/2" x 1 1/2"	2" x 2"					
30 psi	717,000	1,025,000	1,704,000	2,085,000	3,902,000					
50 psi	1,048,000	1,498,000	2,490,000	3,047,000	5,701,000					
75 psi	1,462,000	2,090,000	3,472,000	4,249,000	7,951,000					
100 psi	1,875,000	2,680,000	4,454,000	5,451,000	10,200,000					
125 psi	2,289,000	3,271,000	5,437,000	6,653,000	12,450,000					
150 psi	2,703,000	3,862,000	6,419,000	7,855,000	14,700,000					

TP-P3000BR

REVISION: 5/12