

IS-8-ALL

Series 8 and LF8 Hose Bibb Vacuum Breaker For Backsiphonage Protection

Use only with approved hose bibbs or hose fittings having four or more full American National Hose (NH) threads.

INSTALLATION: For NF8/LFNF8, 8B/LF8B, 8BI/LF8BI and 8FR/LF8FR models, thread onto hose bibb, tighten set screw until head breaks off to provide tamper-resistance. 8A/LF8A and 8P/LF8P models have a built-in non-removable locking feature. Model 8/LF8 is secured by tightening the set screw.

TO DRAIN - 8A/LF8A, 8P/LF8P, 8B/LF8B, 8BI/LF8BI and 8FR/LF8FR can be drained to prevent freezing by removing hose and pulling down gently on the stem. NF8/LFNF8 can be drained by pulling down gently on the black ring and does not require the removal of the hose. Model 8/LF8 is non-draining.

Model 8FR/LF8FR includes built-in freeze protection of the HBVB.

IMPORTANT: Do not use with continuous pressure or use where discharge of water could cause damage.

NOTE: "C" Suffix denotes Chrome



IS-8-ALL

Series 8 and LF8 Hose Bibb Vacuum Breaker For Backsiphonage Protection

Use only with approved hose bibbs or hose fittings having four or more full American National Hose (NH) threads.

INSTALLATION: For NF8/LFNF8, 8B/LF8B, 8BI/LF8BI and 8FR/LF8FR models, thread onto hose bibb, tighten set screw until head breaks off to provide tamper-resistance. 8A/LF8A and 8P/LF8P models have a built-in non-removable locking feature. Model 8/LF8 is secured by tightening the set screw.

TO DRAIN - 8A/LF8A, 8P/LF8P, 8B/LF8B, 8BI/LF8BI and 8FR/LF8FR can be drained to prevent freezing by removing hose and pulling down gently on the stem. NF8/LFNF8 can be drained by pulling down gently on the black ring and does not require the removal of the hose. Model 8/LF8 is non-draining.

Model 8FR/LF8FR includes built-in freeze protection of the HBVB.

IMPORTANT: Do not use with continuous pressure or use where discharge of water could cause damage.

NOTE: "C" Suffix denotes Chrome



IS-8-ALL

Series 8 and LF8 Hose Bibb Vacuum Breaker For Backsiphonage Protection

Use only with approved hose bibbs or hose fittings having four or more full American National Hose (NH) threads.

INSTALLATION: For NF8/LFNF8, 8B/LF8B, 8BI/LF8BI and 8FR/LF8FR models, thread onto hose bibb, tighten set screw until head breaks off to provide tamper-resistance. 8A/LF8A and 8P/LF8P models have a built-in non-removable locking feature. Model 8/LF8 is secured by tightening the set screw.

TO DRAIN - 8A/LF8A, 8P/LF8P, 8B/LF8B, 8BI/LF8BI and 8FR/LF8FR can be drained to prevent freezing by removing hose and pulling down gently on the stem. NF8/LFNF8 can be drained by pulling down gently on the black ring and does not require the removal of the hose. Model 8/LF8 is non-draining.

Model 8FR/LF8FR includes built-in freeze protection of the HBVB.

IMPORTANT: Do not use with continuous pressure or use where discharge of water could cause damage.

NOTE: "C" Suffix denotes Chrome



IS-8-ALL

Series 8 and LF8 Hose Bibb Vacuum Breaker For Backsiphonage Protection

Use only with approved hose bibbs or hose fittings having four or more full American National Hose (NH) threads.

INSTALLATION: For NF8/LFNF8, 8B/LF8B, 8BI/LF8BI and 8FR/LF8FR models, thread onto hose bibb, tighten set screw until head breaks off to provide tamper-resistance. 8A/LF8A and 8P/LF8P models have a built-in non-removable locking feature. Model 8/LF8 is secured by tightening the set screw.

TO DRAIN - 8A/LF8A, 8P/LF8P, 8B/LF8B, 8BI/LF8BI and 8FR/LF8FR can be drained to prevent freezing by removing hose and pulling down gently on the stem. NF8/LFNF8 can be drained by pulling down gently on the black ring and does not require the removal of the hose. Model 8/LF8 is non-draining.

Model 8FR/LF8FR includes built-in freeze protection of the HBVB.

IMPORTANT: Do not use with continuous pressure or use where discharge of water could cause damage.

NOTE: "C" Suffix denotes Chrome



IS-8-ALL

Series 8 and LF8 Hose Bibb Vacuum Breaker For Backsiphonage Protection

Use only with approved hose bibbs or hose fittings having four or more full American National Hose (NH) threads.

INSTALLATION: For NF8/LFNF8, 8B/LF8B, 8BI/LF8BI and 8FR/LF8FR models, thread onto hose bibb, tighten set screw until head breaks off to provide tamper-resistance. 8A/LF8A and 8P/LF8P models have a built-in non-removable locking feature. Model 8/LF8 is secured by tightening the set screw.

TO DRAIN - 8A/LF8A, 8P/LF8P, 8B/LF8B, 8BI/LF8BI and 8FR/LF8FR can be drained to prevent freezing by removing hose and pulling down gently on the stem. NF8/LFNF8 can be drained by pulling down gently on the black ring and does not require the removal of the hose. Model 8/LF8 is non-draining.

Model 8FR/LF8FR includes built-in freeze protection of the HBVB.

IMPORTANT: Do not use with continuous pressure or use where discharge of water could cause damage.

NOTE: "C" Suffix denotes Chrome



IS-8-ALL

Series 8 and LF8 Hose Bibb Vacuum Breaker For Backsiphonage Protection

Use only with approved hose bibbs or hose fittings having four or more full American National Hose (NH) threads.

INSTALLATION: For NF8/LFNF8, 8B/LF8B, 8BI/LF8BI and 8FR/LF8FR models, thread onto hose bibb, tighten set screw until head breaks off to provide tamper-resistance. 8A/LF8A and 8P/LF8P models have a built-in non-removable locking feature. Model 8/LF8 is secured by tightening the set screw.

TO DRAIN - 8A/LF8A, 8P/LF8P, 8B/LF8B, 8BI/LF8BI and 8FR/LF8FR can be drained to prevent freezing by removing hose and pulling down gently on the stem. NF8/LFNF8 can be drained by pulling down gently on the black ring and does not require the removal of the hose. Model 8/LF8 is non-draining.

Model 8FR/LF8FR includes built-in freeze protection of the HBVB.

IMPORTANT: Do not use with continuous pressure or use where discharge of water could cause damage.

NOTE: "C" Suffix denotes Chrome



