

For Backflow Testing Applications

Job Name _____

Contractor _____

Job Location _____

Approval _____

Engineer _____

Contractor's P.O. No. _____

Approval _____

Representative _____

Series TK-9A

Backflow Preventer Test Kit

Model TK-9A Backflow Preventer Test Kit is a compact portable device made for testing all reduced pressure zone backflow prevention assemblies and double check valve assemblies. The TK-9A is easily connected to any RPZ device enabling accurate testing of 'zone' differential pressure, relief valve opening differential, fouled check valves or similar problems that visual inspections cannot locate. Accuracy is +/- 2%. The unit includes a carrying case for easy handling and accessibility.

Features

- 4½" (114mm) diameter face gauge with dual scale (0 - 15psi/0-1 bar)
- Test valves: (2) ball valves
(1) needle valve
- Adapters: (3) ¼" threaded coupling adapters
(3) ½" x ¼" bushings
(3) ¾" x ¼" bushings
- Hoses: (3) 3' (914mm) hoses with female-threaded swivel couplings
- 16" (406mm) securing strap
- Moisture resistant operation manual
- Durable carrying case

Pressure-Temperature

Maximum Working Pressure: 175psi (12.1 bar)

Maximum Working Temperature: 210°F (98°C)



G-TB

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.



Backflow Prevention Products

USA: 815 Chestnut St., No. Andover, MA 01845-6098; www.watts.com

Canada: 5435 North Service Rd., Burlington, ONT. L7L 5H7; www.wattscanada.ca

ES-TK-9A 0643

©Watts Regulator Company, 2006