


Blot-O™ Air

Air Freshener



DESCRIPTION

Blot-O Air is uniquely formulated to eliminate, not mask, odors, especially those associated with fuel oils. Instantly deodorizes the air. This product leaves a pleasant, non-lingering fragrance.

Concentrated formulation requires only a light spray to be effective, and can be applied wherever odors become a problem. Particularly effective on odors relative to fuel oil, gasoline, and other petroleum-related spills. Glycolized to actually clean odor bearing particles from the air.

Contains no CFC's or other chlorinated ingredients.

SIZES AND PACKING

STOCK NO.	SIZE	PACKING	WEIGHT/CASE
35-150	16 oz.	12	5.6 lbs.



Specifications

Blot-O™ Air

Blot-O™ Air

Air Freshener

APPROVALS AND LISTINGS

Not applicable.

SPECIFIC USES

Blot-O Air is used to eliminate fuel oil odors due to spills, and leaks.

SPECIFIC APPLICATIONS*

Blot-O Air replaces odors with a sweet, clean scent. Apply on fuel oil, gasoline, and other petroleum spills.

PHYSICAL PROPERTIES


Specific Gravity	.81
Solubility in water:	Complete
Boiling Point (°F)	185°F
Vapor Pressure:	45 psig @ 70°F
Appearance and color:	Clear light amber liquid with pleasant perfume odor.

WARNINGS OR CAUTIONS

- Do not store near fire, heated surfaces, sparks, or flames.
- Read all cautions and directions carefully before using this product.
- Avoid contact with eyes and skin.
- Use in well ventilated areas. Intentional misuse of aerosol products by inhaling concentrated vapors may be harmful or fatal.
- Do not puncture or incinerate container.
- Dispose of can in accordance with Federal, State and local regulations.
- Contents under pressure. Do not store at temperatures over 120°F.

DIRECTIONS FOR USE

SHAKE WELL BEFORE USING...repeat during use. While holding can upright, spray upwards toward the center of the room with a sweeping motion. Point nozzle away from face or clothes. Concentrated formula requires only a light spray.



MATERIAL SAFETY INFORMATION

FOR MORE INFORMATION ON THIS PRODUCT, REQUEST MATERIAL SAFETY DATA SHEET (MSDS) #99

For Delivery by Fax	Call 1-800-942-4636
Internet	See MSDS section of www.herchem.com
Mail	Contact Hercules at address below or any Hercules representative

HMIS Hazard warning 1-2-0-G.

INGREDIENTS	CAS#
Isopropyl Alcohol	67-63-0
Isobutane	75-28-5
Propane	74-98-6
Propylene Glycol	57-55-6
Water	7732-18-5

* For special applications which may not be covered on this or other Hercules literature, please contact Hercules Technical Services Department by phone at 1-800-221-9330 or send a fax to 1-800-333-3456.



HERCULES® <http://www.herchem.com>

Hercules Chemical Company, Inc.

111 South Street, Passaic, NJ 07055-9100

Phone: 800-221-9330 • Fax: 800-333-3456

e-mail: info@herchem.com

