Aqua-Pure

Models:

AP717

In-Line Filtration System

Spec #

Quantity

Applications:

- Sediment*
- Chlorine Taste & Odor
- Scale

Aguar-Public Strate Water Filter Man Displace Task & Oler, Sediment* and Sald Man Displace Task & Oler, Sediment & Oler,

At a Glance:

- Triple action filtration process
- In-line design for fast and easy installation
- Standard 1/4" NPT inlet/outlet connections
- Provides flow rate up to 0.5 GPM
- Manufactured from FDA CFR-21 compliant materials

Product Benefits:

- Designed from pressure tested, high impact plastic
- Designed with specially formulated high adsoption activated carbon media to help provide longer cartridge life and reduction of unwanted chlorine taste and odor
- Designed with premium performance depth pre-filter for high sediment reduction efficiency and longer cartridge life
- Includes proprietary scale and corrosion inhibition system to help protect equipment and ice makers against scale build-up and potential damaging effects of corrosion.
- Tested and certified by NSF International for verification of system design and performance by a recognized third party certifier


Product Specifications:

Model No. (Part No.)	Inlet/ Outlet Size	Dimensions		Approx.	Flow		Мах.	Max.	Standard	Repl.	Degree of
		Height	Diameter	Weight	Rate	Capacity	Water Temp.	Water Pressure	Repl. Ctg. No.	Ctg. Qty.	Filtration
AP717 (55513-12)	1/4" NPT	8-1/4" (21.0 cm)	2-5/16" (5.9 cm)	0.77 lbs. (0.3 kg)	0.5 gpm (1.9 lpm)	1,500 gallons (5,678 liters)	100°F (37.8°C)	125 psi (862 kPa)	N/A	N/A	5 micron nominal

* Claim not tested or certified by NSF








Easy Installation:

CAUTION: Diagram shown is for reference purposes only. Read installation and operation manual prior to



Spec #

Quantity

Model Number

Part Number

Physical Specifications:

- Standard 1/4" NPT inlet/outlet connections
- System is a single vessel design
- System is manufactured from FDA compliant materials
- System has maximum operating pressure of 125 psi (862 kPa) and operating temperature of 100°F (37.8°C)
- System packed with plumbing fittings and installation hardware
- System to be installed on refrigerator/ice-maker cold water line

WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or **after the system.** The contaminants or other substances removed or reduced by this water filter are not necessarily in all users water. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts.

EPA Establishment Number 070595-CT-001

CUNO Incorporated recommends regularly scheduled maintenance and replacement of the filter cartridge(s) in order for the product to perform as advertised/sold. Change the filter cartridge at least every 6 months. Improper installation and maintenance may result in property damage due to water leakage.

Limited Warranty:

CUNO Incorporated warrants that this product is free from defects in materials and workmanship. This limited warranty, together with any and all warranties implied by law, shall be limited to a period of one (1) year from the date of original purchase. This limited warranty does not apply to failures that result from abuse, misuse, alteration or damage not caused by CUNO or failure to properly comply with these installation or cartridge change-out instructions. This limited warranty is subject to exclusions and limitations. Please refer to the Warranty Card provided with the product for details.

Distributed by:



Visit www.nsf.org for the claims associated with products that are NSF listed.



