

Split System Submittal Data

Ceiling Recessed Low Ambient Air Conditioner


System: KS12NB41A Indoor/Outdoor: CS-KS12NB41/CU-KS12NK1A

Grille: CZ-18BT1U

Panasonic
ideas for life

Job Name: _____
Location: _____
Engineer: _____
Submitted to: _____
Submitted by: _____
Reference: _____

Approval: _____
Date: _____
Construction: _____
Unit #: _____
Drawing #: _____



General Data (at 115V)

Power	V/PH/Hz	115/1/60
Circuit Ampacity	(A)	20
Fuse Size, Max.	(A)	20

Compressor	DC Rotary Inverter	
No. used		1
R.L. Amps - L.R.	(A)	12.6-20
Crankcase Heater	(W)	20

Outdoor Unit		
Fan type		Propeller
Dia. (in.) - No. Speeds		15-3/4-1
Type Drive - No. Speeds		DC Motor
No. Poles	(RPM)	8-750
No. Motors	(W)	50-1
CFM	(HIGH)	1059
F.L. Amps	(A)	0.6

Coil Type	Aluminum Fin and Copper Pipe	
Fin Type - Pipe Type	Corrugated Plate-Inner Rifled	
Rows - F.P.I.		2-18.1
Face Area	(sq.ft.)	3.95
Tube Size	(in.)	5/16"

Indoor Unit		
Fan type		Turbo
Dia. & Length (in.) - No. Speeds		12-5/8/5-3/4-1
No. Speeds		3+Auto
No. Poles	(RPM, High)	8-470
No. Motors	(W)	30-1
CFM	(Hi/Med/Low)	235/206/194
Indoor Sound Rating	(Hi) (dB-A)	34
F.L. Amps	(A)	.346

Coil Type	Aluminum Plate Fin & Copper Tube	
Fin Type - Pipe Type	Slit Plate & Inner Rifled	
Rows - F.P.I.		2-18.1
Face Area	(sq.ft.)	2.94
Tube Size	(in.)	9-32"
Drain Connection Size	(in.)	23/32"

Refrigerant	R410A
Lbs. - R410a (outdoor unit)	2.43
Control	Electric Expansion Valve
Connection	Flare
Line Length, Max (ft.)	65
Lift Difference, Max (ft.)	23
Line Size (in O.D. Discharge)	1/4"
Line Size (in O.D. Suction)	3/8"

Dimensions (in.)	H x W x D
Indoor Unit (uncrated)	11-1/16 x 22-5/8 x 22-5/8
(crated)	11-13/32 x 24-13/16 x 28-1/8
Outdoor Unit (uncrated)	21-9/16 x 28-11/32 x 10-1/16
(crated)	23-5/8 x 33-11/16 x 14-1/4

Weight	Indoor	Outdoor
Net	(lbs.) 35.3	77.2
Shipping	(lbs.) 41.9	83.8

Shipping Volume	(cu.ft.) 4.59	6.35
-----------------	---------------	------

Performance Data @ ARI Standard Conditions (115V)

Cooling		
Total Capacity	(BTU/H)	11,900 (3,000-11,900)
Sensible Capacity	(BTU/H)	7,200
Latent Capacity	(BTU/H)	4,700
SEER		16
Dehumidification	(Pints/H)	4.26
Amps	(A)	12.6 (2.5-12.6)
Power Inputs	(W)	1260 (250-1260)
Outdoor Sound Rating	(dB-A)	51

Dimensions

Features

Controls

Remote Controller
Temperature Control

Timer

Night Setback

Air Louver (Horizontal)
(Vertical)

Power Failure Automatic Restart

Self-Diagnosis

Air Filter

Air Clean Apatite Filter

Quiet Operation

Ion Generator

Microprocessor

LCD Wireless Type, Temp. Sensor Built In

IC Thermostat

24 Hr Program; 1HR ON/OFF

Built-In

Manual

Automatic

Built-In

Built-In

Washable, Anti-Mold

Standard

Built-In

Built-In

Options

Refrigerant Line Set

Fresh Air Intake

Air duct Extension

Condensate Drain Pump

Hard Wired Remote Controller

Non-Removeable Locking Remo-con Bracket

Available

Knock-out

N/A

Standard

Available

Available

Operating Range

Cooling

Maximum

Indoor Air Intake Temp. Outdoor Air Intake Temp.

95F DB/71F WB

115F DB

Minimum

67F DB/57F WB

0F DB

