

Heatguard® 110-D Series

The Heatguard 110-D is a Temperature Actuated Mixing Valve that mixes hot water with cold to deliver tempered water at a controlled temperature to 120°F (49°C) maximum and is designed to assist in the prevention of scalding.


The Heatguard 110-D is intended for installation at the water heater to distribute controlled temperature water through a domestic hot water system.

- Delivers water at a maximum of 120°F (49°C) throughout the system: Safer hot water from all outlets.
- Allows the heater to be set at 140°F (60°C) or higher: Greater effective hot water volume yields less chance of legionella within the cylinder.
- Every valve is tested for performance prior to shipping: Specify and install with confidence!
- Robust, low complexity construction: Superior reliability, improved user safety.
- Unique, purpose designed adjuster tool: *Minimizes* unauthorized tampering with valve setting.
- Listed by IAPMO and ASSE: Inspector friendly, peace of mind!

# CASH ACME

### TYPICAL INSTALLATION


To control water temperature at the source of heat (hot water tank) to provide a safe distribution temperature.








# Heatguard® 110-D Series



### **MODELS/SIZES**



Dimensions	А	В	С	D	E	F
Base Valve	4.1 (103)	2.1 (52)	3.0 (76)	*	*	1.6 (41)
1/2" Sweat	4.1 (103)	2.1 (52)	3.0 (76)	4.4 (112)	2.6 (66)	1.6 (41)
3/4" Sweat	4.1 (103)	2.1 (52)	3.0 (76)	4.9 (124)	3.0 (76)	1.6 (41)
1" Sweat	4.1 (103)	2.1 (52)	3.0 (76)	7.2 (184)	4.2 (106)	1.6 (41)

## **CONNECTIONS** (sold separately)

	Sweat 1/2", 3/4" and 1"   Sweat w/ check 1/2" and 3/4"   Barb 1/2", 3/4" and 1"   Barb w/ Check 1/2", 3/4" and 1"   Compression 3/8" OD (1/4" ID), 1/2" ID (5/8" OD)   Compression w/ check 3/8" OD (1/4" ID), 1/2" ID (5/8" OD)   Compression w/ check 3/8" OD (1/4" ID), 1/2" ID (5/8" OD)   Threaded (NPT) 1/2" and 3/4"   Threaded (NPT) w/ check 1/2" and 3/4"   CPVC 1/2" and 3/4"   CPVC w/ Check 1/2" and 3/4"   SharkBite® Connection 1/2" and 3/4"
--	--

### **CERTIFICATIONS**

The Cash Acme Heatguard® 110-D is certified to ASSE 1017 and CSA B125.3. The Cash Acme Heatguard® 110-D is listed by ASSE and IAPMO.



