## The Energy Factor: Electric

| 30 GALLON CAPACITY<br>MODELS  | INSULATION | ESTIMATED<br>YEARLY COST* | ENERGY<br>FACTOR | FIRST HOUR<br>RATING | LEED POINTS |
|-------------------------------|------------|---------------------------|------------------|----------------------|-------------|
| M-2-30R6DS                    | 2          | \$502                     | .93              | 50                   | 1           |
| M-2-30L6DS                    | 2          | \$496                     | .94              | 47                   | 1           |
| M-1-30L6DS                    | 1          | \$502                     | .93              | 47                   | 1           |
| M-2-30U6SS                    | 2          | \$502                     | .93              | 19                   | 1           |
| M-2-WH30L6SS                  | 2          | \$502                     | .93              | 19                   | 1           |
| 40 GALLON CAPACITY<br>MODELS  | INSULATION | ESTIMATED<br>YEARLY COST* | ENERGY<br>FACTOR | FIRST HOUR<br>RATING | LEED POINTS |
| M-2-40S6DS                    | 2          | \$507                     | .92              | 56                   | /           |
| M-2-40T6DS                    | 2          | \$507                     | .92              | 56                   | /           |
| M-2-HE40S6DS                  | 2          | \$502                     | .93              | 57                   | 1           |
| M-2-40L6DS                    | 2          | \$502                     | .93              | 58                   | /           |
| M-1-40L6DS                    | 1          | \$507                     | .92              | 58                   | /           |
| 50 GALLON CAPACITY<br>MODELS  | INSULATION | ESTIMATED<br>YEARLY COST* | ENERGY<br>FACTOR | FIRST HOUR<br>RATING | LEED POINTS |
| M-2-50S6DS                    | 2          | \$507                     | .92              | 67                   | 1           |
| M-2-50T6DS                    | 2          | \$518                     | .90              | 67                   | /           |
| M-2-HE50S6DS                  | 2          | \$502                     | .93              | 67                   | 1           |
| M-2-50L6DS                    | 2          | \$513                     | .91              | 67                   | /           |
| M-1-50L6DS                    | 1          | \$513                     | .91              | 67                   | /           |
| 65 GALLON CAPACITY<br>MODELS  | INSULATION | ESTIMATED<br>YEARLY COST* | ENERGY<br>FACTOR | FIRST HOUR<br>RATING | LEED POINTS |
| M-2-65R6DS                    | 2          | 524                       | .89              | 77                   | /           |
| M-2-HE65R6DS                  | 2          | 513                       | .91              | 77                   | /           |
| 80 GALLON CAPACITY<br>MODELS  | INSULATION | ESTIMATED<br>YEARLY COST* | ENERGY<br>FACTOR | FIRST HOUR<br>RATING | LEED POINTS |
| M-2-80R6DS                    | 2          | \$530                     | .88              | 92                   | /           |
| M-2-HE80R6DS                  | 2          | \$513                     | .91              | 92                   | /           |
| 120 GALLON CAPACITY<br>MODELS | INSULATION | ESTIMATED<br>YEARLY COST* | ENERGY<br>FACTOR | FIRST HOUR<br>RATING | LEED POINTS |
| M-2-120R6DS                   | 2          | \$549                     | .85              | 118                  | /           |

<sup>\*</sup> Calculated using the updated National Average Fuel Cost.

**LEED** - Leadership in Energy and Environmental Design

**LEED** is a third-party, nationally accepted standard for green building design

- Information supplied by The Gas Appliance Manufacturers' Association and Bradford White.
- The Energy Factor Chart is subject to change without notice in accordance with our policy of continuous improvement.

Last Revised September 9, 2008

