

Model NRC111(GQ-C3257WX US) Series Residential Condensing Tankless Water Heater Specification Sheet

- **Standard Input** - Gas consumption ranges from 16,000 BTUH to 199,900 BTUH
- **Capacity Range**- Flow rates from 0.5 gpm up to 11.1 gpm
- **Compact Design** - ANSI Z21.10.3/CSA 4.3 certified design that can be wall-mounted indoors or outdoors
- **Durable Steel Casing with Polyester Coating**
- **Heat Exchanger** - Manufactured with commercial grade copper, 25% thicker piping than standard models
- **Venting Options** - Available as an Outdoor (requires no venting) or indoor Direct Vent (-DV) model which includes special plastic flue adapters that are compatible with both 3" or 4" Schedule 40 and 80 PVC/CPVC pipe. The DV model can also be converted to an SV model with the use of a Conversion Kit (#SV-CK-3)
- **Direct Electronic Ignition**
- **Quick-Connect**- Two identical units can be linked together by using the optional Quick Connect Cord (#QC-2) for twice the hot water capacity
- **Energy Factor** - 0.91 (NG) 0.91 (LP) for DV model
0.93 (NG) 0.93 (LP) for OD model
- **Temperature Controls** - Includes remote thermostat that can precisely adjust the output temperature from 100°F to 140°F with the capability to display temperatures in both °C and °F
- **Power Cord Installation Kit** - 6' power cord is included with -DV models only
- **Safety Devices** - Flame Sensor, Overheat Prevention Device, Lightning Protection Device, Freeze Protection, Condensate Overfill
- **Additional Features** - Temperature Lockout, High Elevation Adjustment, Condensate Overflow Monitoring System, Service Reminder Function
- **12-Year* Limited Heat Exchanger Warranty for Residential Use**
- **5-Year Limited Parts Warranty**
- **1-Year Reasonable Labor**
- **Approvals** - CSA, UPC**, NSF, Low NOx Approved by SCAQMD [<14ng/J or 20ppm]



OD Model

DV Model


<p>Model NRC111 _____</p> <p><input type="checkbox"/> OD (Outdoor Vent)</p> <p><input type="checkbox"/> DV (Direct Vent)</p> <p>Accessories</p> <p><input type="checkbox"/> Horizontal Hood Termination (#PVT-HL)</p> <p><input type="checkbox"/> 3" PVC Termination (#VK3-H-PVC)</p> <p><input type="checkbox"/> Birdscreen for 3" PVC/CPVC (#VT3-PVCS)</p> <p><input type="checkbox"/> Birdscreen for 4" PVC/CPVC (#VT4-PVCS)</p> <p><input type="checkbox"/> Condensate Neutralizer (#NC-1)</p> <p><input type="checkbox"/> Isolation Valves (#IK-WV-200-1-(SW / TH)-LF)</p> <p><input type="checkbox"/> Pipe Cover (#PC-3S)</p> <p><input type="checkbox"/> Quick Connect Cord (#QC-2)</p> <p><input type="checkbox"/> SV Conversion Kit (#SV-CK-3)</p>



*Heat Exchanger warranty is maintained at 12 years or 6500 operational hours, whichever occurs first, when used in a single family dwelling in conjunction with a controlled recirculation system (an aquastat being the minimum pump control requirement) in accordance with the Installation Manual. Refer to the Noritz Limited Warranty for complete coverage details

**This product complies with California AB 1953 Low Lead Law and Section 1417(d) of the Safe Drinking Water Act


Dimensions



Flow Rates

Temperature Rise (°F)	30	40	45	50	60	70	80	90	100
Flow Rate (GPM)	11.1	9.3	8.4	7.4	6.2	5.3	4.6	4.1	3.7

Pressure Loss



Specifications

Model Name		NRC1111OD (GQ-C3257WX US)	NRC1111DV (GQ-C3257WX-FF US)
Weight		66 (pounds)	68 (pounds)
Operating Pressure		15 - 150 psi	
Gas Supply Pressure		NG: 4.0" - 10.5" LP: 8.0" - 14.0"	
Water Holding Capacity		0.5 Gallon (2 L)	
Connection Sizes	Water Inlet	3/4"	
	Hot Water Outlet	3/4"	
	Gas Inlet	3/4"	
	Condensate Drain	1/2" Threaded	
Power	Supply	120VAC (60Hz), less than 4 amperes	
	Consumption	NG: 78W LP: 80W Freeze Prevention 223W	NG: 81W LP: 83W Freeze Prevention 223W
Freeze Protection		Outdoor: -4°F	Indoor: -30°F
Temperature Settings	°F Mode	100-140°F (In 5°F intervals) (9 Options)	
	°C Mode	37-48°C (In 1°C intervals), 50, 55, 60°C (In 5°C intervals) (15 Options)	
Default Temperature Options	°F Mode	120, 125, 130, 140 °F (Default is 50°F)	
	°C Mode	50, 52, 55, 60°C (Default is 50°C)	