



E CLASS HARD STARTS

E Class



Coupling state of the art electronic potential relay technology and a safety timing circuit, the Elite 'E' Class Hard Start series provide the most reliability of any Hard Start devices.

BENEFITS

- Electronic Potential Relay Technology
- Backup electronic timing circuit to protect the compressor
- Voltage sensing
- Instant re-start
- Easy 2-wire connection

5 ELITE VERSIONS

Providing a solution for any HVAC/R application

- | | | |
|----------|-----------------------------|-------------|
| • SPP4E | Recommended for 1/8 to 1hp | 90V - 130V |
| • SPP5E | Recommended for 1/3 to 2 hp | 170V - 277V |
| • SPP6E | Recommended for 1/2 to 3 hp | 170V - 277V |
| • SPP7E | Recommended for 1 to 4 hp | 170V - 277V |
| • SPP8E | Recommended for 1 to 5 hp | 170V - 277V |
| • SPP9E | Recommended for 1 to 5 hp | 170V - 277V |
| • SPP10E | Recommended for 3 to 5 hp | 170V - 277V |



SEALED UNIT PARTS CO., INC.
PO Box 21, 2230 Landmark Place, Allenwood, NJ USA
732-223-6644 • Fax 732-223-1617
www.supco.com • info@supco.com



APPLICATIONS

For use on any single phase air conditioning and refrigeration unit. See specifications below for voltage ranges and recommended equipment sizes.

SPECIFICATIONS

	Operating Voltage	Recommended Range	Capacitor
SPP4E	90V – 130V	1/8 hp to 1 hp	88 – 106 μ F
SPP5E	90V – 277V	1/3 hp to 2 hp	43 – 52 μ F
SPP6E	90V – 277V	1/2 hp to 3 hp	88 – 106 μ F
SPP7E	90V – 277V	1 hp to 4 hp	130 – 156 μ F
SPP8E	90V – 277V	1 hp to 5 hp	189 – 227 μ F
SPP9E	90V – 277V	1 hp to 5 hp	233 – 280 μ F
SPP10E	90V – 277V	3 hp to 5 hp	270 – 324 μ F/ 330V

COMPETITIVE COMPARISON

	E Class SPPE's	Kickstart®	ICM 850, 860	PTC Devices
Start Sensing Technology	Voltage	Voltage	Voltage	N/A
Uses Electronic Potential Relay	Yes	No	Yes	No
Instant Re-Start	Yes	Yes	Yes	No
Senses Motor Start	Yes	Yes	Yes	No
Two wire, non-polarized	Yes	Yes	Yes	Yes
Replaces 3-wire capacitor kit	Yes	Yes	Yes	Yes
UL approved	Yes	Yes	Pending	Yes
PTCR Device	No	No	No	Yes
Backup Timing Safety Circuit	Yes	No	Yes	N/A
Potentially damaging to motor windings	No	Yes	No	No
Requires non-replaceable fuse protection	No	No	Yes	No

SEALED UNIT PARTS CO., INC.

PO Box 21, 2230 Landmark Place, Allenwood, NJ USA

732-223-6644 • Fax 732-223-1617

www.supco.com • info@supco.com

F277-1102